





FACE MASK BUILD INSTRUCTIONS **TOOLS & MATERIAL LIST**







Adhesive Metal Aluminum Nose Strips X1












- Cut out cloth template and join together using tape.
- Use the pencil and ruler to mark out the template on to
- Using the template, cut 2 copies.













- Iron the two cut outs flat.
- Lay the two mask cut outs on top of each other.
- Iron the two mask cut outs flat again.













- Use a straight stitch on all sewn parts in the design.
- Sew along the top edge. (A)
- Sew along the bottem edge. (B)
- Leave the ends open.
- Trim loose threads.












1cm from the top edge


- Fold the tabs back on themselves and iron flat. Flip the mask over.
- Once again, fold the tabs back on themselves and iron flat.
- Peel backing from the metal nose wire and stick down 1cm from the top edge.














- Fold the mask inside out so the the seams are on the inside (not visible).
- Tip: Use the ruler or pencil to poke the corners out.
- Iron the mask flat.















- Cut out the clear panel template.
- Cut out the scaffold template.
- Use the clear panel template to cut out one panel from the clear flexible sheet.
- Use the the scaffold template to cut out one scaffold from the rigid clear sheet.









Apply a small amount of glue to one side of the scaffold.







Lay the clear flexible panel on top of the scaffold, lining up the outside edges.

INSTRUCTIONS


 Use the glue stick to glue the two clear cut outs together. Tip: Use a small amount of glue as this is only to help hold the panels together before being sewn into place.







TOOLS





- Insert the glued panel into to the cloth mask through the opening.
- Position the glued panel to cover the opening in the centre of the mask.













- Sew around the edge of the opening
- neat edge. (see A)
 Trim any loose threads.


(through the folded tabs) to hold the clear panel in place. Tip: Make sure the cloth tabs stay folded in to give a













INSTRUCTIONS Fold the top of the mask over 3 cm. Iron flat.












INSTRUCTIONS Sew along the folded edge to lock in place. (A)


Trim any loose threads.













INSTRUCTIONS Fold the bottom of the mask over 10 cm. Iron flat.













INSTRUCTIONS Sew along the folded edge to lock in place. (B) Trim any loose threads.














INSTRUCTIONS Fold the bottom part of the mask in half (5cm). Iron flat to fix the crease.














INSTRUCTIONS Fold the bottom part of the mask back on itself 5cm. Iron flat to fix the crease.














- Fold the side of the mask over 1cm. (A)
- Iron flat to fix the crease.
- Fold the side of the mask over again 3cm. (B)
- Iron flat to fix the crease.












- Sew vertically along the folded edge to lock the side in place.
- Tip: The bottom of the mask can be quite thick. Use a little more force to run the stitch over this area.
- Trim any loose threads.








1 cm fold (A)






- Repeat these steps for the other side of the mask.
- Fold the side of the mask over 1cm. (A)
- Iron flat to fix the crease.
- Fold the side of the mask over again 3cm. (B)
- Iron flat to fix the crease.








This area can be thick








- Sew vertically along the folded edge to lock the side in place.
- Tip: The bottom of the mask can be quite thick. Use a little more force to run the stitch over this area.
- Trim any loose threads.








Toggle,





- Add toggles for fit adjustment.
- Poke the elastic in to the top and bottom openings 1cm (A,B,C,D)
 Sew over the elastic 3 times to lock in place.
- INSTRUCTIONS



